



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DW-7611BT0591

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of water supply <i>Produkte der Wasserversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Georg Fischer Fittings GmbH Mariazeller Straße 75, A-3160 Traisen
Distributor <i>Vertreiber</i>	Georg Fischer Fittings GmbH Mariazeller Straße 75, A-3160 Traisen
Product Category <i>Produktart</i>	metal pipe unions and joints : malleable cast iron fittings with compression ends for polyethylene (PE) piping systems (7612)
Product Description <i>Produktbezeichnung</i>	compression fitting made of galvanized cast iron for pipes made of PE or PE-Xa for the drinking water supply
Model <i>Modell</i>	PRIMOFIT
Test Reports <i>Prüfberichte</i>	supplement test: 120004603 from 27.08.2015 (MPM) supplement test: 411.334-4 from 20.08.2014 (OFM) supplement test: 411.334-3k from 10.06.2014 (OFM) type testing: 120003149-1 from 11.12.2008 (MPM) type testing: 120003149-2 from 10.12.2008 (MPM) KTW testing: K-255053-15-Ko/st from 24.03.2015 (WHY)
Test Basis <i>Prüfgrundlagen</i>	DVGW GW 335-B4/(P) (01.04.2014) DIN EN 10284 (01.08.2000) UBA METALLE (02.04.2015) UBA KTW (07.10.2008) DVGW W 270 (01.11.2007)
Date of Expiry / File No. <i>Ablaufdatum / Aktenzeichen</i>	30.04.2020 / 14-0606-WNV

70028-04-A-CE

08.10.2015 Wg A-1/2 
Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.



DVGW CERT GmbH
Zertifizierungsstelle
Josef-Wirmer-Str. 1-3
53123 Bonn
Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993
www.dvgw-cert.com
info@dvgw-cert.com

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
PRIMOFIT	diameter: 20 mm	
PRIMOFIT	diameter: 25 mm	
PRIMOFIT	diameter: 32 mm	
PRIMOFIT	diameter: 40 mm	
PRIMOFIT	diameter: 50 mm	
PRIMOFIT	diameter: 63 mm	

Hints of Utilization / Remarks***Verwendungshinweise / Bemerkungen***

Für pipes made from PE-HD (PE 80 and PE 100) according to DVGW GW 335-A2 and PE-Xa according to DVGW GW 335-A3